Product Specification

SyncSol SHST 2245

Heat Activated Seam Sealing



Description

PRODUCT DESCRIPTION - SyncSol Heat Activated Seam Sealing Tape SHST 2245 is Heat Activated Seam Sealing Tape made from specially treated PE film.
Application: Heat Activated Seam Sealing Tape is specially made for use in sealing non-woven fabric seams and is waterproof, dustproof and germ proof. It is mainly used in making non-woven isolation clothes, non-woven working suits and non-woven lab coats. For best results, use 330 °C heated air to press and bond.

Application Technique: For best results, ensure the surface is clean, dry and dust free before application of the tape. Apply even and firm pressure for better adhesion results.

MAIN APPLICATIONS - SyncSol Heat Activated Seam Sealing Tape SHST 2245 is Heat Activated Seam Sealing Tape made from specially treated PE film. It is mainly used in making non-woven isolation clothes, non-woven working suits and non-woven lab coats.

Technical Data

Base Material	Specially Treated PE Film
Total Thickness	150 µm
Breaking Strength (kg / cm2)	≥ 200
Tensile Strength (kg / cm2)	250
Elongation	600 %
Backing Material Fusion Point	110 °C ±10 °C
Glue Fusion Point	80 °C
Colour	Blue
Size Available	20 mm x 200 m

Storage & Shelf Life: The tape should be stored in cool and dry place and prolonged exposure to the direct sunlight should be avoided. To obtain best performance, the product should be used within 12 months from the date of manufacture.

For latest information on this product please https://www.adhesive.syncsolinc.com/

The technical values are determined by/based on standard tests. Our recommendations on the use of the product are based on reliable in-house tests, but the users are requested to conduct their own test to determine the suitability of the product. SyncSol will not be responsible for any loss or damage caused as a result of our recommendations. SyncSol products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore SyncSol can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the SyncSol product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

In our endeavors to continuously improve the product from time to time, the data indicated are subject to change. Current details should be therefore checked with SyncSol.

WhatsApp +91-98918 70805

For enquiry and quotation processing please submit your request to enquiry@syncsolinc.com

www.syncsolinc.com | www.adhesive.syncsolinc.com | www.trading.syncsolinc.com