Product Specification

SyncSol MHTP 6332

High Tempreture Masking Tape



Description

PRODUCT DESCRIPTION - SyncSol Masking Tape High Tempretaure MTHT 6332 is resin impregnated crepe paper coated with high tack pressure-sensitive natural rubber based adhesive. MTHT 6332 enables you to protect nearby surfaces from getting sprayed, resulting in a clean paint lines and can be removed easily and cleanly when finished. It resists solvents or water from the paint, and are strong enough to hang plastic sheeting yet can be taken off easily without damaging the surface or leaving any residue on the surface. The crepe paper backing allows you to finish the curved and irregular surface as well allowing you to get the exact finishing you want. Even on the curvatures. The tape is easy to tear by hand for tool-free application. This ideal masking tape is the quick, easy and efficient products solution for general purpose and high temperature masking, all at an affordable price.

MAIN APPLICATIONS - SyncSol Masking Tape High Tempretaure MTHT 6332 is used in critical paint masking application for the appliance, automotive, furniture, marine, metal working, construction and aerospace industry. The tape is easy to tear by hand for tool-free application. Other applications are automotive holding, protecting, labelling, painting, arts and crafts etc.

Technical Data

▪ Base Material	Resin Impregnated Crepe Paper – 60 gsm
▪ Adhesive	Natural Rubber
▪ Total Thickness	135 µm / 98 gsm
▪ Tensile Strength (kg/mm)	8 kgs / 25 mm
▪ Elongation (% at break)	9 %
▪ Adhesion to Steel (gms/inch)	750 gms
▪ Temperature Resistance(°C/hr.)	120 °C
▪ Roll Ball Tack	1.5 cms

Storage & Shelf Life: The tape should be stored in cool and dry place and prolonged exposure to the direct sunlight should be avoided. To obtain best performance, the product should be used within 12 months from the date of manufacture.

For latest information on this product please https://www.adhesive.syncsolinc.com/

The technical values are determined by/based on standard tests. Our recommendations on the use of the product are based on reliable in-house tests, but the users are requested to conduct their own test to determine the suitability of the product. SyncSol will not be responsible for any loss or damage caused as a result of our recommendations. SyncSol products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore SyncSol can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the SyncSol product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

In our endeavors to continuously improve the product from time to time, the data indicated are subject to change. Current details should be therefore checked with SyncSol.

WhatsApp +91-98918 70805

For enquiry and quotation processing please submit your request to enquiry@syncsolinc.com

www.syncsolinc.com | www.adhesive.syncsolinc.com | www.trading.syncsolinc.com