
Product Specification

SyncSol SSST 2240

Seam Sealing Tape



Description

Description : SyncSol Seam Sealing Tape SSST 2240 is specially developed adhesive tape for seam sealing application in coveralls and Protective wear made from non woven fabrics.SyncSol Seam Sealing Tape SSST 2240 is made out of specially treated Polyester film and antibacterial adhesive.SyncSol Seam Sealing Tape SSST 2240 is suitable to be used at room temperature and has fast bonding with high adhesion for high performance.

SyncSol Seam Sealing Tape SSST 2240 is counted among the top Antibacterial Seam tape manufacturers in India because we offer versatile antibacterial seam tape. This type of waterproof tape is highly beneficial for applications where sealing the fabric seam is crucial, such as sealing the PPE suits of Doctors and other health professionals working in a highly infectious environment.

Safe and Efficient Antibacterial Seam Tape

As We are the Leading Seam Sealing Tape Manufacturers, We specialize in adhesives and tape manufacturing. And we have made this antibacterial seam tape after extensive global research to maximise the safety quotient. We have utilized high-quality materials as we never compromise with quality while manufacturing our products, especially when it comes to the health and safety of our customers.

High Performance and Unbeatable Quality

SyncSol Adhesive is known for providing high-performance products and antibacterial seam tape is the prime example of that. We are appreciated for delivering the right product at the right time for our customers. With such an approach in our working methodology, we have become the leading Antibacterial seam tape supplier in India in a quick time.

Technical Data

Base Material	Specially Treated PP Film – 25 µm
Adhesive	EVA
Coating Thickness	65 µm
Total Thickness	90 µm
Elongation (machine direction)	50 %
Adhesion to Steel (gms/inch)	900 gms
Adhesion to Steel (gms/inch)	3,000 gms
Heat Resistance (°C/hr.)	60 °C
Roll Ball Tack	1 cm
Advantage	Waterproof and Antibacterial

Storage & Shelf Life: The tape should be stored in cool and dry place and prolonged exposure to the direct sunlight should be avoided. To obtain best performance, the product should be used within 12 months from the date of manufacture.

For latest information on this product please https://www.adhesive.syncsolinc.com/

The technical values are determined by/based on standard tests. Our recommendations on the use of the product are based on reliable in-house tests, but the users are requested to conduct their own test to determine the suitability of the product. SyncSol will not be responsible for any loss or damage caused as a result of our recommendations. SyncSol products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All technical information and data above mentioned are provided to the best of our knowledge on the basis of our practical experience. They shall be considered as average values and are not appropriate for a specification. Therefore SyncSol can make no warranties, expressed or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is responsible for determining whether the SyncSol product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

In our endeavors to continuously improve the product from time to time, the data indicated are subject to change. Current details should be therefore checked with SyncSol.

WhatsApp +91-98918 70805

For enquiry and quotation processing please submit your request to enquiry@syncsolinc.com

www.syncsolinc.com | www.adhesive.syncsolinc.com | www.trading.syncsolinc.com